



DITCH SHALL BE 1.5 FEET DEEP MIN. A DEPTH OF 5 FEET IS REQUIRED FOR CULVERT CROSSINGS. PLACE CHECK DAMS AT REGULAR INTERVALS FOR ROAD GRADES IN EXCESS OF 5%.

MATCH EXISTING GRADE

AGGREGATE BASE SHALL BE DENSE GRADED, $\frac{3}{4}$ " - 0 CRUSHED ROCK, 8 INCHES COMPACTED THICKNESS, COMPACTED TO 95% OF THEORETICAL MAXIMUM DRY DENSITY PER AASHTO T-99.

$\frac{1}{2}$ " DENSE, LEVEL 2 HOT MIX ASPHALT CONCRETE PLACED IN TWO 2-INCH LIFTS, FOUR INCHES COMPACTED THICKNESS.

SHOULDERS SHALL BE SHALL BE $\frac{3}{4}$ " - 0 DENSE GRADED CRUSHED ROCK, FOUR INCHES COMPACTED THICKNESS AT OUTER EDGE.

PROVIDE A FIRM AND WELL FORMED SURFACE ON WHICH AGGREGATES ARE TO BE PLACED. ALL SUBGRADE MATERIAL SHALL BE COMPACTED TO 95% OF OPTIMUM DENSITY. REMOVE AND REPLACE SOFT SPOTS WITH APPROVED MATERIAL.

TYPICAL COLLECTOR OR COMMERCIAL SECTION

NOT TO SCALE

CROOKED RIVER RANCH, OREGON

AUGUST 2022